

## OIL SEPARATOR. TURBOCLEAN SS WMF. Made in Germany

### TURBO CLEAN SS WMF.

This version are made to Order and is an excellent system that can be used for perfect For CNC machines tramp oil maintenance in house

This oil separator is made of stainless steel and sheet steel. The 15-liter tank for separated oil can be removed without tools.

MODEL	TURBOMIX CLEAN SS	
Hydraulic Capacity	250 l/h	
Oil Removal	35l/h	
Electrical Connection	230V,50Hz,0.45Kw,3.5A	
Dimension	L750XW50XH950mm	DIGITAL / NON DIGITAL

TURBOCLEAN SS is the ultimate power tool in machine shops where CNC machines are in continuous use and with the tramp oil contaminating the fluids causing wastage and to make it easier the TURBOCLEAN SS is the Problem solver for trouble free operations.

#### How it Works.

The fluid surface is drawn off by suction using a skimmer. The skimmer is self-regulating and adjusts continually to the fluid surface and is attached to the KSS tank with a magnet. The removed fluids are gently transferred to a sedimentation tank. The oil separator is subject to minimal wear as the removed oils and emulsions do not come into contact with rotating parts. It has optimal and continuous oil removal. The oil separator is switched off automatically when the maximum level in the oil collecting tank is reached

